


OSB5513

3pce Stainless Steel Full Port Direct Mount Ball Valve
 -1/2"-2" 1000 WOG
 -4°F to 392°F
 -Blow-out proof stem
 -anti-static device
 -Investment Casting
 -Socket Weld End Connections
 -ISO-5211 Direct Mount



ITEM	PARTS	MATERIAL	
1	BODY	ASTM A351-CF8M	ASTM A216-WCB
2	CAP		
3	BALL	ASTM A351-CF8M	
4	RETAINER		
5	STEM	ASTM A276-316	
6	SEAT	RTFE	
7	SEAL	PTFE	
8	THRUST WASHER		
9	PACKING	VITON	
10	O-RING		
11	BELLEVILLE WASHER	AISI 301	
12	HANDLE	AISI 304	
13	LOCKING PAD		
14	GLAND RING		
15	LOCKING WASHER		
16	BOLT		
17	NUT		
18	SPRING WASHER		
19	STEM NUT		



OC12345.2C

NPS	d	d1	D	L	L1	H	H1	H2	H3	W	S	A	D1	D2	D3	R1	R2	ISO 5211	Torquo(N-M)
1/4"	0.31	0.57	0.87	2.17	0.43	2.48	0.31	1.59	0.26	4.72	0.35	1.65	1.22	1.42	1.65	0.11	0.11	F03/F04	31.9
3/8"	0.39	0.7	0.87	2.36	0.43	2.48	0.31	1.59	0.26	4.72	0.35	1.65	1.22	1.42	1.65	0.11	0.11	F03/F04	31.9
1/2"	0.59	0.87	1.14	2.95	0.39	2.48	0.31	1.59	0.26	4.72	0.35	1.65	1.22	1.42	1.65	0.11	0.11	F03/F04	31.9
3/4"	0.79	1.08	1.38	3.15	0.51	2.72	0.35	1.77	0.26	4.72	0.35	1.65	1.22	1.42	1.65	0.11	0.11	F03/F04	54
1"	0.98	1.35	1.65	3.54	0.51	2.99	0.39	1.87	0.3	5.83	0.43	1.97	1.4	1.65	1.97	0.11	0.14	F04/F05	87.6
1-1/4"	1.26	1.69	2.05	4.33	0.51	3.31	0.43	2.19	0.3	5.83	0.43	1.97	1.4	1.65	1.97	0.11	0.14	F04/F05	138.1
1-1/2"	1.5	1.93	2.44	4.72	0.51	3.9	0.47	2.57	0.35	7.01	0.55	2.76	2.2	1.97	2.76	0.14	0.18	F05/F07	194.7
2"	1.97	2.4	2.95	5.51	0.63	4.25	0.47	2.87	0.35	7.01	0.55	2.76	2.2	1.97	2.76	0.14	0.18	F05/F07	237.2

OS&B® Industrial

13-495 Woodward Ave., Hamilton, Ontario, Canada L8H 6N6

T. 1.905.661.0976 F. 1.905.667.1842

All rights reserved. OS&B® Industrial reserves the right to change product specifications and material or discontinue models without notice.

www.osbindustrial.ca